

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 981 263 A2

EUROPEAN PATENT APPLICATION

(12)

(43) Date of publication:  
23.02.2000 Bulletin 2000/08

(51) Int Cl.7: H05B 3/74, H05B 1/02

(21) Application number: 99306125.8

(22) Date of filing: 02.08.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Wilkins, Peter Ravenscroft  
Droitwich, Worcestershire WR9 7DU (GB)

(74) Representative: Jackson, Derek Charles  
Derek Jackson Associates  
The Haven  
Plough Road  
Tibberton Droitwich  
Worcestershire WR9 7NQ (GB)


(30) Priority: 14.08.1998 GB 9817646

(71) Applicant: Ceramaspeed Limited  
Droitwich, Worcestershire WR9 7DJ (GB)

(54) Radiant electric heater

(57) A radiant electric heater includes a base (2) of thermal and electrical insulation material having a surface supporting at least one heating element (3) in the form of an elongate electrically conductive ribbon (4). The ribbon (4) is supported on edge and is partially embedded in the surface of the base (2). A rod-like temperature-responsive device (7, 8) extends at least partly

across the heater from an edge of the heater and over the at least one heating element (3). The surface of the base (2) is provided with a shallow recess (9) beneath the rod-like temperature-responsive device (7, 8) and the ribbon (4) is partially embedded in the shallow recess (9) to a lesser extent than in the surface of the base (2) at either side of the shallow recess.



EP 0 981 263 A2

## Description

[0001] This invention relates to radiant electric heaters, particularly but not exclusively for use in cooking appliances behind a sheet of a material such as glass-ceramic. In particular, the sheet of material such as glass-ceramic may be a cooking surface.

[0002] Radiant electric heaters are well known for use behind glass-ceramic cooking surfaces. Such heaters can comprise a dish-like support having therein a base layer of insulation material, such as microporous thermal and electrical insulation material. At least one electrical heating element is provided, supported on the surface of the base layer. One form of heating element which has found wide acceptance is an elongate electrically conductive ribbon which is supported on edge and partially embedded in the surface of the base layer.

[0003] It is known to provide a temperature-responsive device of rod-like form extending at least partly across the heater from an edge thereof and overlying the heating element or elements. Such temperature-responsive device operates to control the operation of the heater, such as to prevent the glass-ceramic material of the cooking surface reaching a high temperature at which damage would occur thereto.

[0004] It is important that the temperature-responsive device should primarily respond to the temperature of the cooking surface rather than to direct thermal radiation from the heating element or elements. It is known to reduce the direct thermal radiation from the heating element or elements on the temperature-responsive device by arranging for a strip of the surface of the base layer directly beneath the device to be free from the heating element or elements. This is achievable when it is possible to provide the heating element or elements in a pattern whereby suitable reversals are arranged in the pattern such that there is no traversal of the element or elements beneath the temperature-responsive device.

[0005] However there are situations where this cannot be achieved. One in particular is where at least one heating element is provided configured as a spiral, which may be a double spiral. With such an arrangement it is unavoidable that passage of the element or elements occurs beneath the temperature-responsive device. This means that the full radiation power of the heating element or elements is directly incident on the temperature-responsive device and furthermore the heating element or elements reach a locally higher temperature directly beneath the temperature-responsive device compared with other regions of the heater. This may cause premature failure of the element or elements as well as premature switching of the limiter.

[0006] It is an object of the present invention to overcome or reduce these problems.

[0007] According to the present invention there is provided a radiant electric heater comprising a base of thermal and electrical insulation material having a surface

supporting at least one heating element in the form of an elongate electrically conductive ribbon, the ribbon being supported on edge and partially embedded in the surface of the base, and a rod-like temperature-responsive device extending at least partly across the heater from an edge thereof and over the at least one heating element, wherein the surface of the base is provided with a shallow recess beneath the rod-like temperature-responsive device, and wherein the ribbon is partially embedded in the shallow recess to a lesser extent than in the surface of the base at either side of the shallow recess.

[0008] As a result of the invention, the at least one heating element operates at a reduced temperature beneath the rod-like temperature-responsive device thus avoiding premature failure of the element or elements and also providing a correspondingly reduced direct thermal influence on the device.

[0009] The at least one heating element where partially embedded in the shallow recess may present an upper surface plane which is substantially coplanar with an upper surface plane presented by the at least one heating element at either side of the shallow recess.

[0010] The shallow recess may be substantially in the form of a channel.

[0011] The base may comprise microporous thermal and electrical insulation material.

[0012] The at least one heating element may be generally in the form of a spiral which may be a double spiral.

[0013] The at least one heating element in the form of the elongate electrically conductive ribbon may incorporate a plurality of spaced-apart support members, such as legs which may be integral with the remainder of the ribbon, extending edgewise from the remainder of the ribbon and being at least partially embedded in the surface of the base.

[0014] For a better understanding of the present invention and to show more clearly how it may be put into effect reference will now be made, by way of example, to the accompanying drawings in which:

Figure 1 is a plan view of a radiant electric heater according to the invention; and

Figure 2 is a cross-sectional view of part of the heater of Figure 1.

[0015] A radiant electric heater comprises a metal dish 1 having provided therein a base layer 2 of thermal and electrical insulation material, preferably microporous thermal and electrical insulation material. A radiant electric heating element 3 is provided comprising a corrugated ribbon 4, such as of iron-chromium-aluminium alloy, incorporating spaced-apart legs 5 integral therewith and extending edgewise therefrom. Alternatively, the ribbon may incorporate separate legs which are secured to the remainder of the ribbon. The heating element is mounted edgewise on the base layer 2 and secured by partial embedding in the surface of the base

layer 2. This is achieved by pressing the legs 5 on the corrugated ribbon 4 at least partly into the surface of the base layer 2, the technique being known in the art. As shown, the heating element is of double spiral form, but may be of another suitable form.

[0016] A peripheral wall 6 of insulation material is provided in the heater and has a top surface which may be arranged to contact the rear side of a glass-ceramic cooking surface (not shown) in a cooking appliance.

[0017] A temperature limiter of well known form is provided on the heater and comprises a rod 7 extending over the heating element and operating a switch arrangement 8 at the edge of the heater. Such temperature limiter is operable at a predetermined temperature to de-energise the heating element to prevent overheating particularly of a glass-ceramic cooking surface when the heater is operated therewith.

[0018] In the absence of the present invention the heating element 3, where it passes beneath the rod 7 of the temperature limiter, operates at a locally higher temperature than the remainder of the element and this, coupled with the close proximity of the element 3 to the rod 7, results in premature failure of the element and also premature switching of the temperature limiter.

[0019] In the present invention this disadvantage is minimised or reduced by providing a shallow recess 9 in the surface of the base layer 2 directly beneath the rod 7 of the temperature limiter. The shallow recess 9 is substantially in the form of a channel having a depth of, for example, 1 to 2 mm. Where the heating element 3 crosses the shallow recess 9, the legs 5 on the corrugated ribbon 4 are embedded in the base layer 2 to a lesser extent than are those legs on the ribbon at either side of the shallow recess 9. For example, where the heating element crosses the shallow recess the legs 5 may be embedded to a depth of about 1 mm whereas elsewhere they may be embedded to a depth of about 2 mm.

[0020] This arrangement does not alter the overall profile of the heating element, since the element where partially embedded in the shallow recess presents an upper surface plane 10 which is substantially coplanar with an upper surface plane 11 presented by the heating element at either side of the shallow recess 9.



[0021] As a result of the arrangement, the heating element has a greater exposed surface area and consequently a reduced temperature where it crosses the shallow recess 9 in the base layer 2 directly beneath the rod 7 of the temperature limiter. This advantageously prevents premature failure of the heating element 3 and also reduces the direct influence of the heating element on the rod 7 of the temperature limiter.

surface supporting at least one heating element (3) in the form of an elongate electrically conductive ribbon (4), the ribbon being supported on edge and partially embedded in the surface of the base (2), and a rod-like temperature-responsive device (7, 8) extending at least partly across the heater from an edge thereof and over the at least one heating element (3), characterised in that the surface of the base (2) is provided with a shallow recess (9) beneath the rod-like temperature-responsive device (7, 8), and in that the ribbon (4) is partially embedded in the shallow recess (9) to a lesser extent than in the surface of the base (2) at either side of the shallow recess.

2. A heater according to claim 1, characterised in that the at least one heating element (3), where partially embedded in the shallow recess (9), presents an upper surface plane (10) which is substantially coplanar with an upper surface plane (11) presented by the at least one heating element (3) at either side of the shallow recess (9).
3. A heater according to claim 1 or 2, characterised in that the shallow recess (9) is substantially in the form of a channel.
4. A heater according to claim 1, 2 or 3, characterised in that the base (2) comprises microporous thermal and electrical insulation material.
5. A heater according to any preceding claim, characterised in that the at least one heating element (3) is generally in the form of a spiral.
6. A heater according to claim 5, characterised in that the spiral comprises a double spiral.
7. A heater according to any preceding claim, characterised in that the at least one heating element (3) in the form of the elongate electrically conductive ribbon (4) incorporates a plurality of spaced-apart support members (5) extending edgewise from the remainder of the ribbon and being at least partially embedded in the surface of the base (2).
8. A heater according to claim 7, characterised in that the spaced-apart support members comprise legs (5).
9. A heater according to claim 8, characterised in that the legs (5) are integral with the ribbon (4).

#### Claims

1. A radiant electric heater comprising a base (2) of thermal and electrical insulation material having a



(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

EP 0 981 263 A3

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
27.09.2000 Bulletin 2000/39

(51) Int Cl.7: H05B 3/74, H05B 1/02

(43) Date of publication A2:  
23.02.2000 Bulletin 2000/08

(21) Application number: 99306125.8

(22) Date of filing: 02.08.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Wilkins, Peter Ravenscroft  
Droitwich, Worcestershire WR9 7DU (GB)

(74) Representative: Jackson, Derek Charles  
Derek Jackson Associates,  
The Old Yard,  
Lower Town  
Claines, Worcester WR3 7RY (GB)


(30) Priority: 14.08.1998 GB 9817646

(71) Applicant: Ceramaspeed Limited  
Droitwich, Worcestershire WR9 7DJ (GB)

(54) Radiant electric heater

(57) A radiant electric heater includes a base (2) of thermal and electrical insulation material having a surface supporting at least one heating element (3) in the form of an elongate electrically conductive ribbon (4). The ribbon (4) is supported on edge and is partially embedded in the surface of the base (2). A rod-like temperature-responsive device (7, 8) extends at least partly

across the heater from an edge of the heater and over the at least one heating element (3). The surface of the base (2) is provided with a shallow recess (9) beneath the rod-like temperature-responsive device (7, 8) and the ribbon (4) is partially embedded in the shallow recess (9) to a lesser extent than in the surface of the base (2) at either side of the shallow recess.



EP 0 981 263 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 6125

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 081 073 A (EGO ELEKTRO BLANC & FISCHER) 15 June 1983 (1983-06-15) * claims 1,2; figures *	1	H05B3/74 H05B1/02
A	US 4 243 874 A (FISCHER KARL) 6 January 1981 (1981-01-06) * column 7, line 3 - line 23; figures 7-9 *	1	
A	US 4 789 772 A (MCWILLIAMS JOSEPH A) 6 December 1988 (1988-12-06) * figure 5 *	1	
A	US 5 393 958 A (GROSS MARTIN ET AL) 28 February 1995 (1995-02-28) * column 5, line 25 - line 46; figures 2,3 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H05B
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>9 August 2000</b>	Examiner <b>Castanheira Nunes, F</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

# ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 99 30 6125

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-08-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0081073 A	15-06-1983	DE 3143692 A	11-05-1983
		AT 18297 T	15-03-1986
		DE 3269441 D	03-04-1986
US 4243874 A	06-01-1981	DE 2729929 A	04-01-1979
		DE 2820138 A	15-11-1979
		AT 105483 A	15-06-1994
		AT 140383 A	15-01-1984
		AT 373990 B	12-03-1984
		AT 449678 A	15-07-1983
		AU 519310 B	26-11-1981
		AU 3736378 A	03-01-1980
		CA 1118029 A	09-02-1982
		CH 634451 A	31-01-1983
		DK 281378 A,B,	03-01-1979
		DK 383883 A,B,	22-08-1983
		DK 531486 A,B,	06-11-1986
		ES 471330 A	01-09-1979
		FI 781901 A,B,	03-01-1979
		FI 831768 A,B,	19-05-1983
		FR 2396243 A	26-01-1979
		FR 2522119 A	26-08-1983
		GB 1600568 A	21-10-1981
		GR 64869 A	05-06-1980
		HK 38383 A	07-10-1983
		IT 1206694 B	27-04-1989
		IT 1098217 B	07-09-1985
		JP 1738465 C	26-02-1993
		JP 2020249 B	08-05-1990
		JP 54014868 A	03-02-1979
		NO 782212 A,B,	03-01-1979
		SE 7806238 A	03-01-1979
		SE 8502584 A	24-05-1985
		YU 155078 A	30-06-1982
		ZA 7803539 A	27-06-1979
US 4789772 A	06-12-1988	AT 84392 T	15-01-1993
		AU 603337 B	15-11-1990
		AU 5990186 A	07-01-1987
		CA 1266293 A	27-02-1990
		DE 3531691 A	11-12-1986
		DE 3687432 A	18-02-1993
		DE 3687432 T	06-05-1993
		DE 8525366 U	10-07-1986
		EP 0206597 A	30-12-1986
		ES 555901 D	16-02-1987

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 6125

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-08-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4789772 A		ES 8703704 A	01-05-1987
		WO 8607519 A	18-12-1986
		JP 7089514 B	27-09-1995
		JP 63500061 T	07-01-1988
		NZ 216459 A	27-10-1989
		US 4910387 A	20-03-1990
		ZA 8604336 A	25-02-1987
-----			
US 5393958 A	28-02-1995	DE 4229373 A	10-03-1994
		AU 667734 B	04-04-1996
		AU 4484793 A	10-03-1994
		CN 1087771 A	08-06-1994
		EP 0585831 A	09-03-1994
		JP 2639783 B	13-08-1997
		JP 6201139 A	19-07-1994
		SI 9300459 A	31-03-1994
		TR 27675 A	16-06-1995
		ZA 9306468 A	22-03-1994
-----			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82